

Series 2, Wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50M



Optional accessories

DWA0KP6A Standard odor filter
DWZ6HP1U2 Standard recirculation kit

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- Quiet extraction with powerful performance
- High extraction rate - for continuously clean air in the kitchen.
- Adjust the extraction intensity according to your cooking needs.
- Dishwasher safe aluminum mesh filters
- Ducted or Non-ducted Options

Technical Data

Color chimney:Stainless steel
Typology:Wall-mounted
Length electrical supply cord: 120.0 cm
Height of the chimney: 410-765/410-765 mm
Height of the appliance: 250 mm
Minimum distance above an electric hob: 650 mm
Minimum distance above a gas hob: 650 mm
Net weight: 9.2 kg
Type of control: Mechanical
Number of speed settings: 3
Max. air extraction: 380 m³/h
Max. air recirculation: 235 m³/h
Maximum Air flow: 380 m³/h
Number of lights: 2
Noise level: 64 dB(A) re 1pW
Diameter of air outlet: 150 mm
Grease filter material: Washable aluminium
EAN code: 4242002985299
Connection rating: 135 W
Voltage: 220-240 V
Frequency: 50 Hz
Plug type: GB plug
Installation typology: Wall-mounted



4 242002 985299

Series 2, Wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50M

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 380 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB*

Features

- 3 power levels
- 2 x LED 5W
- Colour Temperature: 4000 K
- 2 removable metal grease filter cassettes
- Installation: wall

Design

- Chimney extractor hood
- Push button control
- Mechanical

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Maximum extraction rate exhaust air 380 m³/h according to EN 61591
- Extraction rate in recirculation mode:
 - Max. normal use: 235 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Noise level in recirculation mode:
 - Max. normal use: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Power rating: 135 W
- Light Intensity: 1000 lux
- Electrical cable length 1.2 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 790-1015 x 598 x 470 mm
- Dimensions recirculating (HxWxD): 790-1015 x 598 x 470 mm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 72.8 kWh/year*

Optional accessories

- Recirculating kit DWA0KP6A

* In accordance with the EU-Regulation No 65/2014

**Series 2, Wall-mounted cooker hood,
60 cm, Stainless steel
DWP64CC50M**

