

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER
D64MAC1X0B



Optional accessories

Z51IMA0X0 Standard odor filter (replacement)

The Integrated Cooker Hood with a fold out unit is discreetly hidden within the upper cabinets.

✓ LED Lighting – Clear illumination while you cook.

Features

Technical Data

Typology: Built-in/Built-under
Length electrical supply cord: 150.0 cm
Height of the appliance: 402 mm
Minimum distance above an electric hob: 500 mm
Minimum distance above a gas hob: 650 mm
Net weight: 10.8 kg
Type of control: Mechanical
Number of speed settings: 3
Maximum output air extraction: 625 m³/h
Maximum output recirculating air: 416 m³/h
Maximum Air flow: 625 m³/h
Number of lights: 2
Noise level: 70 dB(A) re 1pW
Diameter of air outlet: 150 / 120 mm
Grease filter material: Washable aluminium
EAN code: 4242004223375
Connection Rating: 256 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50; 60 Hz
Plug type: GB plug
Installation typology: Wall-mounted



N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER D64MAC1X0B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- Push button control operation
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 metal grease filter cassettes

Design

- Integrated hood
- Installation: Between Cupboards
- Hinged door
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 68.4 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

Optional accessories

- Recirculating kit Z51IMA0X0

* In accordance with the EU-Regulation No 65/2014

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER
D64MAC1X0B

Dimensioned drawings

