


iQ500, Gas hob, 75 cm, Tempered glass, Black
EP7A6QI40



HZ298105	Simmer plate
HZ298107	Wok ring
HZ298114	Small pot support
HZ32WA00	Wireless food thermometer
HZ9SE040	4 pieces Set
HZ9SE060	6 pieces Set

Tempered glass gas hob with stepFlame Technology for precise flame control, with detachable dials and semi-continuous pan supports for an easy cleaning.

- ✓ stepFlame Technology: Precise flame control with nine different settings
- ✓ Black tempered glass surface: Extremely heat-resistant
- ✓ Detachable metallic sword dials: Easily removable for easy cleaning and precise cooking control
- ✓ Semi-continuous pan support: Easy to handle and easy to clean
- ✓ Wok burner with 4.0 kW: Fast cooking with even heat distribution

Product name/family: gas hob w
integrated controls
Built-in / Free-standing: Built-in
Source of energy: Gas
Number of cooking zones: 5
Required niche size for installation (HxWxD):45 x 560-562 x
480-492 mm
Width of the appliance: 752 mm
Dimensions: 54x752x520 mm
Dimensions of the packed product (HxWxD): ... 168 x 798 x 596 mm
Weight: 19.9 kg
Gross weight: 22.4 kg
Residual heat indicator:without
Location of control panel: Front
Basic surface material: Tempered glass
Color of surface: Black
Color of frame: Black
Length electrical supply cord: 100.0 cm
EAN code:4242003966778
Gas connection rating: 11500 W
Fuse protection:3 A
Nominal power:220-240 V
Frequency:50; 60 Hz



iQ500, Gas hob, 75 cm, Tempered glass, Black EP7A6QI40

Design

- Tempered Glass surface, black
- frameless design: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports with rubber feet
- full metal

Usage convenience

- Step Flame technology - 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner gas hob including:
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 4 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.
- Cast iron pan supports with rubber feet: little weight and compact form, yet high stability due to continuous surface.

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 54 x 752 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- If installed flush, minimum worktop thickness is 30mm.
- Power cord: 1 m
- Connected load: 11.5 KW

**iQ500, Gas hob, 75 cm, Tempered
glass, Black
EP7A6QI40**

