

N 90, Downdraft hood, 80 cm, clear glass  
188WMM1Y7B




COOKING PASSION SINCE 1877



The Glass Draft Hood seamlessly integrates into the kitchen, with ability to install behind the hob for a single surface look and clear glass panel when in use. Powered by new Guided Air technology for effective extraction, and Climate Control Sensor to optimise the power and noise levels as you cook.

- ✓ Guided Air Technology – Equally powerful steam extraction all over the cooktop regardless of the pans' or pots' location
- ✓ Glass Panel with Illumination – 25 million colour options for inspiring illumination of your cooktop
- ✓ Easy Access Filter – A simple push of a button is enough to remove the easy access filter for a good wash in the dishwasher
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology
- ✓ Cooktop-based Hood Control – Adjust your hood's extraction level and lighting.



## Features

### Technical Data

Typology : Downdraft  
Length of electrical supply cord : 130.0 cm  
Min. required niche size for installation (HxWxD) : 703mm x 781.0mm x 123mm mm  
Net weight : 43.0 kg  
Type of control : Electronic  
Number of speed settings : 3-stage + 2 intensive  
Maximum output air extraction : 501 m<sup>3</sup>/h  
Boost position output recirculating : 525 m<sup>3</sup>/h  
Maximum output recirculating air : 416 m<sup>3</sup>/h  
Boost position air extraction : 775 m<sup>3</sup>/h  
Noise level : 62 dB(A) re 1 pW  
Diameter of air outlet : 150 mm  
Grease filter material : Washable stainless steel  
EAN code : 4242004270782  
Connection rating : 300 W  
Fuse protection : 10 A  
Voltage : 220-240 V  
Frequency : 50-60 Hz  
Plug type : GB plug  
Installation type : Built-in  
Delay Shut off modes : 10M min

## Optional accessories

|           |                                        |
|-----------|----------------------------------------|
| Z861SB1   | 90° flat duct bend horizontal          |
| Z861SB2   | 90° flat duct L vertical               |
| Z861SI0   | Adapter round-flat                     |
| Z861SI1   | 90° Adapter round-flat                 |
| Z861SM1   | Straight tube 500mm                    |
| Z861SM2   | Straight tube 1000mm                   |
| Z861SS1   | Connector sleeve (female)              |
| Z92WWI1X6 | Clean Air Plus recirculation kit       |
| Z92WWJ11  | Long Life recirculation kit            |
| Z92WWM11  | Installation kit remote motor          |
| Z92WWY8X2 | Mounting kit for seamless installation |



4 242004 270782

N 90, Downdraft hood, 80 cm, clear glass  
I88WMM1V7B



COOKING PASSION SINCE 1877

## Features

### Variant

- 80 cm wide
- Installation: integrated
- Suitable for ducted extraction and recirculation

### Design

- Extendable clear glass panel with edge lighting
- Flex design: Exchangeable side trims, available in various colours and lengths (not included in the standard delivery)
- edges illuminated
- Pure surface design: suitable for seamless installation to create a unity look with the cooktop (special accessories required)

### Comfort

- Touch control
- The standard functions are located on the right-hand user interface
- Touch control for extractor speeds and light
- 3 power levels and 2 intensive settings
- Automatic revert setting
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 minutes))
- climateControl Sensor
- Hob-Hood control (with Wi-Fi enabled hob)
- Fully automatic hood

### Features

- Additional functions: Ambient light RGB
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- The filter service button automatically lifts filters into service position for easy removal
- The glass panel can be easily removed and cleaned

### Connectivity

- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Silence function: available via Home Connect
- Interval function: available via Home Connect

### Performance

- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use: 501 m³/h  
Intensive: 775 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 62 dB(A) re 1 pW  
Intensive: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:  
Extraction rate in recirculation mode: Max. normal use: 416 m³/h  
Intensive: 525 m³/h  
Noise level in recirculation mode: Max. normal use: 65 dB(A) re 1 pW  
Intensive: 70 dB(A) re 1 pW
- Efficient BLDC technology

### Planning and installation information

- Suitable for installation in an island or Semi-island kitchen solution
- Suitable for installation into 90 cm cabinet
- Please reference the built-in dimensions provided in the installation drawings
- For recirculated extraction Clean Air Plus recirculation kit (accessory) needed
- For remote motor installation, special accessory kit (Z92WWM11) is needed
- Not suitable for combination with gas hobs
- Built-in dimensions (HxWxD): 703 x 781 x 123 mm
- Dimensions (HxWxD): 709 x 802 x 140 mm
- Extension height 250 mm
- Extractor hose 150 mm
- Electrical cable length 1.3 m

### Consumption Data


- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 36.9 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: -\*
- Grease Filtering Efficiency Class: B\*
- Power rating: 300 W



N 90, Downdraft hood, 80 cm, clear glass  
188WMM1V7B


Dimensioned drawings

Measurements in mm  
Combination with electric hob  
Seamless, top-mounted installation



- A:** Worktop overlap to kitchen cabinet  
Combination with gas hob is not possible
- To prevent power loss, observe the following:
- Do not install upper cabinets or open shelf elements above the appliance
  - Left/right distance between appliance and wall/adjacent upper cabinet min. 500 mm

Measurements in mm



- A:** Installation of motor unit on front/rear or offset laterally with max. 3 m clearance (special accessory required)
- Motor unit must always be accessible
- B:** 5.5 mm  
**C:** Special accessory required